

ORAJET® Series 3675 Perforated Window Graphics Inkjet Media (50/50)

Description

Perforated, 5.5-mil PVC film available in white with a gloss finish and black backing. 50% printable area.

Release Paper

83# Silicone paper

Adhesive

Clear, solvent-based, permanent adhesive

Applications

For short- and medium-term window graphics applications

Technical Data

Thickness (without protective paper and adhesive)	5.5 mil
Dimensional Stability (FINAT TM-14)	Adhered to steel, no shrinkage in cross direction; In length, <.016"
Temperature Resistance	Adhered to glass, -40°F to +176°F, no variation
Seawater Resistance (DIN 50021)	Adhered to glass, 48 hours, 73°F, no variation
Adhesive Power (FINAT TM-1, after 24 h, average)	Adhered to steel: 2.7 lb/in ²
Tensile Strength (DIN EN ISO 527) Along Across	Min. 5 MPa/725 psi Min. 5 MPa/725 psi
Elongation at Break (DIN EN ISO 527) Along Across	Min. 50% Min. 50%
Shelf Life (68°C/50% relative humidity)	2 years
Minimum Application Temperature	50°F
Available Lengths Available Widths (inches)	164' (50 meters) and 10 yards 24, 30, 54,
Minimum Life Expectancy (based on accepted application procedures on vertical surfaces)	3 years
Recommended Laminate	ORAGUARD® Series 290F

For up-to-date color profiles, please visit our website at www.oracal.com.

Attention

Surfaces to which the material will be applied must be cleaned thoroughly of dust, grease or any contaminants. Freshly lacquered or painted surfaces should be allowed to stand for at least three weeks after complete curing. The compatibility of selected lacquers and paints should be tested by the end-user prior to use.

The statements in this information sheet are based upon our knowledge and practical experience. This data is intended only as a source of information and is given without any guarantee and does not constitute a warranty. Due to the wide variety of possible uses and applications, customers should independently determine the suitability of this material for their specific purpose, prior to use.

