

ORAJET[®] Series 3951 Professional Wrapping Film With Rapid Air[™] Technology

Description

2-mil cast PVC film available in white with gloss finish

Release Paper

80# PE-coated silicone paper featuring advanced air-release technology to facilitate quicker, easier application

Adhesive

Grey, solvent-based, repositionable, permanent adhesive that can be removed with little or no adhesive residue for up to four years

Applications

Designed specifically to conform to irregular surfaces such as vehicle wraps and other fleet applications

Technical Data

Thickness (without protective paper and adhesive)	2 mil
Dimensional Stability (FINAT TM-14)	Adhered to steel, no shrinkage in cross direction; In length, <.009"
Temperature Resistance	Adhered to aluminum, -58°F to +230°F, no variation
Fire Behavior (DIN 75200)	Adhered to steel, self-extinguishing
Adhesive Power (FINAT TM-1, after 24 h, average)	Adhered to stainless steel: 4.1 lb/in ²
Tensile Strength (DIN EN ISO 527) Along Across	Min. 19 MPa/2755 psi Min. 19 MPa/2755 psi
Elongation at Break (DIN EN ISO 527) Along Across	Min. 120% Min. 120%
Seawaterability (DIN 50 021)	Adhered to aluminum, after 100h/73°F, no variation
Shelf Life (68°C/50% relative humidity)	2 years
Minimum Application Temperature	46°F
Available Lengths Available Widths (inches)	164' (50 meters) 15, 30, 36, 48, 54, 54RW, 60
Minimum Life Expectancy (based on accepted application procedures on vertical surfaces)	10 years
Recommended Laminates	ORAGUARD [®] Series 290 or Series 290F (vehicle) Series 240 (outdoor signage and banners)

For up-to-date color profiles, please visit our website at www.oracal.com.

Attention

Surfaces to which the material will be applied must be cleaned thoroughly of dust, grease or any contaminants. Freshly lacquered or painted surfaces should be allowed to stand for at least three weeks after complete curing. The compatibility of selected lacquers and paints should be tested by the end-user prior to use.

The statements in this information sheet are based upon our knowledge and practical experience. This data is intended only as a source of information and is given without any guarantee and does not constitute a warranty. Due to the wide variety of possible uses and applications, customers should independently determine the suitability of this material for their specific purpose, prior to use.

DISTRIBUTED BY: J WALKER SIGN SUPPLY 1-800-248-8872



ORACAL USA

7251 Salisbury Road
Jacksonville, FL 32256 USA
Toll Free 800.672.2251
904.726.9597 • FAX 904.726.9409
www.oracal.com • ORACAL USA 2006